

TATAMI Screen



COMPOSITION 50% polypropylene,
35% acrylic, 15% polyester

WIDTH 188cm

WEIGHT 280gsm

PATTERN REPEAT Nil

ROLL SIZE 50m (approx)

CARE CODE Screens

CTA RATING  **COMMERCIAL
SCREEN FABRICS**

LIGHTFASTNESS 6/7
ISO 105-B02

FIRE RATINGS
AS 1530 Pt.3

Ignitability	13
Spread of Flame	0
Heat Evolved	3
Smoke Developed	3

AS/NZS 3837
(Cone Calorimeter)

BCA Group 2
Av. Specific Extinction area 177.2 m2/kg

NO. OF COLOURS 15

USE Screens and panels

ENVIRONMENTAL BENEFITS

RAW MATERIALS

- 50% low embodied-energy material: polypropylene has a lower embodied-energy compared to polyester and nylon.

PRODUCTION

- Environmentally Improved Production Process: reduced energy consumption, reuse & recycling of waste

GREEN STAR

- TATAMI can be used on white furniture certified to Ecospecifier's GreenTag GreenRate standard (Levels B + C), AFRDI's Sustainability Standard for Commercial Furniture and GECA Furniture and Fittings Standard.
- The Green Star Rating Tool states "Where at least 90% of an item's total mass is certified to a GBCA recognised standard, the item can be entered as a certified product at Level A, B or C". Any fabric can be used as fabrics are almost always under 10% by weight of a furniture item.